





This is to certify that: FrameXpress Limited

Unit E4

Tweedale Industrial Estate

Madeley Telford TF7 4JR

United Kingdom

Holds Certificate Number: KM 824697

In respect of:

BS 4873/PAS 24 Enhanced Security Aluminium Window Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI: Shahm Barhom, Group Product Certification Director

First Issued: 2025-07-09 Effective Date: 2025-07-09 Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 1 of 9



No. KM 824697

BS 4873:2016 / PAS 24:2022 - Enhanced security performance requirements for windows in the UK.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Smart System under Certificate Number KM 81580.

Alitherm 400 Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm 400 Window Manual

System description:

The windows are thermally broken, internally or externally beaded, with at least one pane of laminated glass meeting the requirements of BS EN 356:2000, Class P1A or higher, where applicable, and shall be glazed in accordance with the BS 6262 series where required, multipoint locking only, with mechanically fixed transoms/mullions. The fitting of any connected or smart device to this product will invalidate this Kitemark Certificate unless BSI has been provided with objective evidence from a competent authority that the device has been tested and certified to EN 303645. BSI will update any Kitemark certificates with the relevant products as and when they have been

tested.

Window Types: Casement windows

Tilt/Turn windows Fixed windows

Multilight windows comprising opening light(s) and/or dummy vent(s) or fixed light(s)

Profiles: Outer Frame(s) ETC4110/4112/4115/4111/4113/4117/4011/4014/4210

Transom/Mullion(s) ETC4130/4135/4136/4031/4230/4232/4236

Sash(es) ETC4120/4129/4124/4021/4229

Rebate Reverser ETC4146/4147

First Issued: 2025-07-09 Effective Date: 2025-07-09
Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 2 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Hardware - Alitherm 400 Aluminium Alloy Window System Casement windows*

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Friction Hinge Securistyle Defender/Sterling Nico ME-Egress Hinge (Yale)	Smart Systems	ACET070	Smart Systems
Securistyle/Yale hinge protector ASD/ASD-ST	Smart Systems	ACET066	Smart Systems
Trojan and ERA Shootbolt/mushroom bolt espagnolette locking system, ERA hook lock	Smart Systems	Espagnolette & keeps: ACET067	Smart Systems
Casement Key locking handles	Smart Systems	ACET069	Smart Systems
Run-up blocks 4 off per sash	-		

^{*}Glass retention as specified below.

Tilt/Turn Windows

Sobinco Chrono Invision Safe Tilt/Turn gearing Sobinco scissor stay	Smart Systems	Integral within gearing	Smart Systems
Tilt/Turn Key locking handles	Smart Systems	ACET069	Smart Systems

Dummy vent windows*

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Securistyle Defender stays	Smart Systems	ACET070	Smart Systems

^{*}Glass retention as specified below.

Glass retention: External: Glazing beads and Glaslok Securi-clip security glazing clips

> Internal: Glazing beads

Multilight windows comprising opening light(s) and/or dummy vent(s) or fixed light(s)

Hardware/Fixing requirements are as specified for opening, dummy vent and fixed window types.

First Issued: 2025-07-09 Effective Date: 2025-07-09 Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 3 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Alitherm 400 Aluminium Alloy Window System Classification for Operational strength in accordance with BS 6375

Operating forces	Class 1
Resistance to Static Torsion	Class 3
Racking	Class 3
Load Bearing capacity of safety devices	Pass
Impact Resistance	Class 0
Resistance to opening and closing	Class 2



First Issued: 2025-07-09 Effective Date: 2025-07-09 Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 4 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Externally Beaded

ETC4130/4135 T/M

ETC4130/4135 T/M

Externally Beaded

Internally Beaded

Multilights

Multiliahts

Alitherm 400 Aluminium Alloy Window System Size Limitations and Performance Characteristics — to be read in conjunction with fabrication manual

Exposure category Friction Stays (up frame - Maximum **Transom/Mullion** As given in Table of BS 6375-1: to and including) Length (mm) inc Air Permeability Watertightness Window Type classification classification Resistance to classification Length (mm) Height (mm) - Maximum Maximum Area(m²) Wind Sash dimensions for windows with approved sash profiles: Projecting top hungs 24" 1400 1500 4 E1200 AE2400 2000+ Internally beaded Projecting top hungs 1400 1500 24" 4 E1200 AE2400 2000+ Externally beaded Projecting side hungs 1000 1400 16" 4 E1200 AE2400 2000+ Internally beaded Projecting side hungs 1000 1400 16" 4 E1200 AE2400 2000+ Externally beaded 1200 2100 4 9Α BF2400 Tilt/Turn 2000+ Overall dimensions for windows with approved outer frame profiles: **Fixeds** 2100 2100 4.2 4 E1200 AE2400 2000+ **Internally Beaded Fixeds** AE2400 2100 2100 4.2 4 E1200 2000 +

BS 4873:2016 has been issued by BSI under a flexible accreditation scope

Overall dimensions for approved outer frames & transom/mullion profiles:

2100

2100

2100

2100

First Issued: 2025-07-09 Effective Date: 2025-07-09
Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

2.5

2.5

1450

1450

4

4

E1200

E1200

AE2400

AE2400

2000 +

2000 +

Page: 5 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

BS 4873:2016 / PAS 24:2022 - Enhanced security performance requirements for windows in the UK.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Smart System under Certificate Number KM 81580.

Alitherm Heritage & Alitherm Heritage HD Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm Heritage & Alitherm Heritage HD Window Manual

System description:

HD Profiles:

The windows are thermally broken, internally or externally beaded, with at least one pane of laminated glass meeting the requirements of BS EN 356:2000, Class P1A or higher, where applicable, and shall be glazed in accordance with the BS 6262 series where required, multipoint locking only, with mechanically fixed transoms/mullions. The fitting of any connected or smart device to this product will invalidate this Kitemark Certificate unless BSI has been provided with objective evidence from a competent authority that the device has been tested and certified to EN 303645. BSI will update any Kitemark certificates with the

relevant products as and when they have been tested.

Window Types: Casement windows

Tilt/Turn windows Fixed windows

Multilight windows comprising opening light(s) and/or dummy vent(s) or fixed light(s)

Profiles: Outer Frame(s) W20015/20016/20017/20018/W20110

Transom/Mullion(s) W20032/20034/20035/20037/20039/W20130/W20131/

W20133/W20139

Sash(es) W20024/20025/20026/20028/20029/W20120/20122

Rebate Reverser W20047/20147
Outer Frame(s) W20310/20317

Transom/Mullion W20330/20331/20332/20333/20135N

Sash(es) W20320/20325

Rebate Reverser W20345

First Issued: 2025-07-09 Effective Date: 2025-07-09
Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 6 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Hardware -Alitherm Heritage & Alitherm Heritage HD Aluminium Alloy Window System Casement windows*

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Friction Hinge – Securityle Defender Sterling Nico ME-Egress Hinge	Smart Systems	ACET070	Smart Systems
Securistyle/Yale hinge protector ASD/ASD-ST	Smart Systems	ACET066	Smart Systems
Shootbolt/mushroom bolt espagnolette locking system ACW201-205 (ACW301-306 HD profiles)	Smart Systems	Espagnolette & keeps: ACET066	Smart Systems
Casement Key locking handles	Smart Systems	ACET069	Smart Systems
Run-up blocks 4 off per sash	-		

Tilt/Turn windows

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Sobinco Chrono invision safe tilt turn gearing , Sobinco Scissor Stay.	Smart Systems	Integral within gearing	Smart Systems
Tilt/Turn Key Locking Handles	Smart Systems	ACET069	Smart Systems

Dummy vent windows*

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Securistyle Defender stays	Smart Systems	ACET070	Smart Systems

Glass retention: Glazing beads and Glaslok Securi-clip security glazing clips

Internal: Glazing beads

Multilight windows comprising opening light(s) and/or dummy vent(s) or fixed light(s)

Hardware/Fixing requirements are as specified for opening, dummy vent and fixed window types.

First Issued: 2025-07-09 Effective Date: 2025-07-09 Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 7 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Alitherm Heritage & Alitherm Heritage HD Aluminium Alloy Window System Classification for Operational strength in accordance with BS 6375

Operating forces	Class 1
Resistance to Static Torsion	Class 3
Racking	Class 3
Load Bearing capacity of safety devices	Pass
Impact Resistance	Class 0
Resistance to opening and closing	Class 2



First Issued: 2025-07-09 Effective Date: 2025-07-09 Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 8 of 9

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. KM 824697

Alitherm Heritage Aluminium Alloy Window System

Size Limitations and Performance Characteristics – to be read in conjunction with fabrication manual **Transom/Mullion** Length (mm) inc given in Table to and including) irame - Maximum Air Permeability classification **Natertightness** Window Type Resistance to classification classification of BS 6375-1 Length (mm) Height (mm) Area(m²) Maximum - Maximum Maximum Friction Stays **Exposure** Sash dimensions for windows with approved sash profiles: Projecting top hungs 1400 1400 24" 4 AE2400 2000+ 7A Internally beaded Projecting top hungs 1400 1400 24" 4 9A AE2400 2000+ Externally beaded Projecting top hungs HD 7A Int 1750 1400 4 AE2400 2000+ Int/Ex Beaded 9A Ex Projecting side hungs 900 16" 4 7A 1400 AE2400 2000+ Internally beaded Projecting side hungs 16" 900 1400 9A AE2400 2000+ 4 Externally beaded Projecting side hungs HD 7A Int 2000+ 838 1750 AE2400 4 Int/Ex Beaded 9A Ex Tilt/Turn 1200 2100 4 9A BE2400 2000+ Internally beaded Overall dimensions for windows with approved outer frame profiles: **Fixeds** 2100 2100 4.2 4 7A AE2400 2000+ **Internally Beaded Fixeds** 4 2100 2100 4.2 9A AE2400 2000+ **Externally Beaded** Overall dimensions for approved outer frames & transom/mullion profiles: Multilights W2035 T/M 2100 2100 2.5 1450 4 7A AE2400 2000+ **Internally Beaded** Multilights W2035 T/M 2000+ 2100 2100 2.5 1450 4 9A AE2400 **Externally Beaded**

BS 4873:2016 has been issued by BSI under a flexible accreditation scope

2100

2100

Multilights W21030 T/M

Internally Beaded

First Issued: 2025-07-09 Effective Date: 2025-07-09
Latest Issue: 2025-07-09 Expiry Date: 2028-07-08

Page: 9 of 9

AE2400

2000+

4

7A

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.